



SPORTEC® UNI outdoor

VERSATILE SURFACE FOR OUTDOOR AREAS

SPORTEC® UNI outdoor is a durable flooring suitable for various types of applications. It is the ideal surface for outdoor multi-purpose sports areas due to its high resilience and excellent durability against mechanical impact. **SPORTEC® UNI outdoor** for sports applications can be used with or without elastic underlay. In case of high shock absorbance required **SPORTEC® standard** can be used as elastic underlay. The combination of **SPORTEC® UNI outdoor** and **SPORTEC® standard** is offered as **SPORTEC® UNI sandwich outdoor**.

Technical Data:

Material:	Coarse-grained coloured EPDM granules bonded with polyurethane elastomer.
Colours:	dark-grey, red, blue, green, beige (other colours on request)
Surface:	coarse granule structure
Colour grades:	100% coloured EPDM granules
Width:	1,250 mm (± 1.5%)
Thickness:	4 mm (± 0.3 mm) (other thicknesses on request)
Volumetric weight:	approx. 1,095 kg/m ³
Roll length:	30 m (± 1.5%)
Tensile Strength:	approx. 0.6 MPa (DIN 53577)
Elongation at break:	approx. 60% (EN ISO 1798)
Hardness:	60 ± 5 Shore A (DIN 53505)
Compression set:	approx. 15% (DIN 53517)
Fire Resistance:	C _{fl} s1 (EN 13501-1)

Standard colours:

dark-grey



red



blue



green



beige





SPORTEC® UNI sandwich outdoor

PREVENTING JOINT DAMAGES AND INJURIES

SPORTEC® UNI sandwich outdoor is a combination of our well-engineered elastic layer **SPORTEC® standard** and our **SPORTEC® UNI outdoor** floor covering. This combination offers a maximum protection and safety while preventing joint damages and injuries. It proves its perfect suitability as outdoor sports surfacing for basketball, volleyball and multipurpose fields.

Technical Data:

Material: Surface: coarse-grained EPDM granules bonded with polyurethane elastomer
Underlay: fine rubber granules bonded with polyurethane elastomer

Colours: surface available in green, blue, red, dark-grey and beige (other colours on request)
Underlay: black

Width: Surface: 1,250 mm (± 1.5%)
Underlay: 1,500 mm (± 1.5%)

Thickness: Surface: 4 mm (± 0.3 mm)
Underlay: standard thickness of SPORTEC® standard (other thicknesses on request)

Roll length: Surface: 30 m (± 1.5%)
Underlay: standard length (other length on request)

Tensile strength*: 0.7 N/mm² (EN 12230)

Elongation at break*: 59% (EN 12230)

Resistance to wear*: 2.9 g (ISO 5470-1)

Colour change*: 4 (ISO 105-A02)

Friction (dry/wet)*: 101/56 (EN 13036-4)

Vertical deformation*: 0.6 (EN 14809)

Ball rebound*: 100% (EN 14877)

Standard colours surface:

dark-grey



red




blue



green



beige



* Test results for UNI sandwich outdoor with 4 + 4 mm thickness



SPORTEC® easy track

THE SURFACING SOLUTION FOR TEMPORARY TRACK-AND-FIELD FACILITIES

SPORTEC® easy track is a portable temporary sports track surfacing for outdoor warm-up areas and event locations. **SPORTEC® easy track** can be installed over solid or granular subsurfaces. Equally well suited for indoor applications, **SPORTEC® easy track** provides ideal temporary or seasonal surfacing on sports floors to prevent damage by spiked shoes in winter months. It is available with a geotextile layer on lower side for protection of damage-sensitive subsurfaces.

SPORTEC® easy track is tested according to the IAAF specifications for track and field facilities and provides other unbeatable benefits including simple installation, fast removal and easy stackability and storage when not in use. Installation does not require specially trained personnel nor does it require special equipment. Convenient connector pins ensure fast installation and secure placement.

Technical Data:

Material:	polyurethane-bonded recycled tyre rubber granules
Reinforcing mesh:	glass fibre
Geotextile mat:	polyester geotextile mat (on request)
Colour:	red-brown
Surface:	grain-structure
Lower side:	smooth with drainage channels
Dimensions:	500 x 500 x 30 mm (± 3 mm)
Volumetric weight:	approx. 28 kg/m ²
Tensile strength:	approx. 0.75 N/mm ²
Elongation at break:	approx. 70% (EN ISO 1798)
Wear resistance:	rV 5.9 (DIN 18035 part 6)
Fire resistance:	E _{fl} (B2) (EN 13501-1)
Cold fracture resistance:	24 h/-40° C, no fracture
Cold crack resistance:	5 h/-30° C, no cracks





ZAYAANCO

Suite No. 704, Orange Tower,
Next to National Paint Factory, P. O. Box
72936, Sharjah, U.A.E.
Hotline : +971 5555 6 4004
Tel No. : +971 6 569 17 57
info@zayaanco.com, www.zayaanco.com

Bespoke design flooring in UAE I Pool surrounds flooring specialist Sharjah I Recycled rubber interlock flooring stockiest RAK I Virgin PVC interlock gym flooring traders Dubai I Recycled rubber flooring companies UAE I Interlock rubber flooring play area installers Dubai I On site playground flooring companies Abu Dhabi I School play area flooring contractor Dubai I Outside play area rubber flooring companies UAE I Pre- School flooring installer Dubai I Nursery flooring Dubai I Kindergarten flooring specialist Sharjah I Gym flooring manufacturer Sharjah I Sports flooring specialist Dubai I Basketball flooring suppliers Dubai I Interlocking stud tiles manufacturer Abu Dhabi I Pool mats stockiest Sharjah I Interlocking slate rubber tiles supplier Ajman I No slip rubber flooring stockiest Fujairah I Round stud tiles installers UAQ I Coin type vinyl tiles supplier Al Ain I Coin type rubber tiles manufacturer Al Ain I Modular floor tiles supplier Dubai I Pad and Pour flooring Dubai I Wet area flooring Sharjah I Colorful coin grip rubber flooring company RAK I Commercial rubber flooring manufacturer RAK I Garage rubber floor UAE I Soft tiles traders Ajman I Virgin rubber tile flooring contractor Abu Dhabi I Interlocking rubber gym flooring Abu Dhabi I Styrene Butadiene Rubber (SBR) flooring specialist Dubai I Ethylene Propylene Diene Monomer (EPDM) flooring companies Dubai I Anti-skid rubber flooring installers Abu Dhabi I Kennel flooring UAE I Anti-slip mats Dubai I Anti-fatigue mats Dubai I Flooring Adhesives in Dubai I Self leveling contractors in UAE I Flooring installer in Abu Dhabi I Flooring contractors Dubai I Flooring suppliers in Dubai I Flooring solutions Dubai I Acoustic multi-layer flooring solutions Dubai I Educational acoustic Dubai I Antistatic flooring UAE I Commercial flooring Abu Dhabi I Contract flooring Dubai I Bespoke design flooring in UAE I Pool surrounds flooring specialist Sharjah I Recycled rubber interlock flooring stockiest RAK I Virgin PVC interlock gym flooring traders Dubai I Recycled rubber flooring companies UAE I Interlock rubber flooring play area installers Dubai I On site playground flooring companies Abu Dhabi I School play area flooring contractor Dubai I Outside play area rubber flooring companies UAE I Pre-School flooring installer Dubai I Nursery flooring Dubai I Kindergarten flooring specialist Sharjah I Gym flooring manufacturer Sharjah I Sports flooring specialist Dubai I Basketball flooring suppliers Dubai I Interlocking stud tiles manufacturer Abu Dhabi I Pool mats stockiest Sharjah I Interlocking slate rubber tiles supplier Ajman I No slip rubber flooring stockiest Fujairah I Round stud tiles installers UAQ I Coin type vinyl tiles supplier Al Ain I Coin type rubber tiles manufacturer Al Ain I Modular floor tiles supplier Dubai I Pad and Pour flooring Dubai I Wet area flooring Sharjah I Colorful coin grip rubber flooring company RAK I Commercial rubber flooring manufacturer RAK I Garage rubber floor UAE I Soft tiles traders Ajman I Virgin rubber tile flooring contractor Abu Dhabi I Interlocking rubber gym flooring Abu Dhabi I Styrene Butadiene Rubber (SBR) flooring specialist Dubai I Ethylene Propylene Diene Monomer (EPDM) flooring companies Dubai I Anti-skid rubber flooring installers Abu Dhabi I Kennel flooring UAE I Anti-slip mats Dubai I Anti-fatigue mats Dubai I Flooring Adhesives in Dubai I Self leveling contractors in UAE I Flooring installer in Abu Dhabi I Flooring contractors Dubai I Flooring suppliers in Dubai I Flooring solutions Dubai I Acoustic multi-layer flooring solutions Dubai I Educational acoustic Dubai I Antistatic flooring UAE I Commercial flooring Abu Dhabi I Contract flooring Dubai I