

# APS FUEL TANK RANGE



## FUEL TANKS

APS have been manufacturing fuel tanks in the UAE since 2011, APS fuel tanks are built under the ADR / UN requirements (PPG2 & PPG26) Codes. APS fuel tanks are built & tested to the highest standards within the industry & are certified by a 3rd party company like Bureau Veritas. APS is now in partnership with Untied Engineering Services LLC (UES) in Oman, who is also one of the most respected engineering companies within the oil & gas industry. UES manufactures the APS range of fuel tanks for the MENA areas.

## FEATURES

### Small Tank Range

- Tanks are fabricated from high grade mild steel
- 2 x Feed and Return Fuel Fittings. (  $\frac{1}{2}$  or  $\frac{3}{4}$  fuel fittings)
- 3" Fuel Fill Point with Fuel Cap for easy filling
- 2 Way Fork Lift Pockets and 4 Point Lift Hooks are provided for easy and safe handling
- Frame designed for Multi Stacking for economical storage and transportation in Containers & Truck Beds
- Space efficient design: Can easily stack up to 2 high when full and 3 High when empty
- Internal Baffles included in all tanks to prevent Fuel Surge
- Unique Hex Corners for extra strength and Hose Openings in front to allow tank to be used when locked

### Large Tank Range

- Tanks are manufactured in 20ft & 40ft ISO Containers.
- 4 x ISO Lifting Points on Containers.
- 2 x hydrostatic fuel indicator for inner tank & outer bunded tank.
- 6 x Feed & Return Fuel Line Fittings. (1" Standard Fittings)
- 3" Cam Lock Fuel Fill Point.
- 600mm Manway with Access Ladder for easy Maintenance.
- Over fill and wet alarm indicator.
- Fuel Safe Spillage Containment. (Bunded to 110%)
- Standard Container Access Door at Front of Container.

TANK RANGE	FUEL CAPACITY LITRES	SAFE FILL LEVEL LITRES	DIMENSION			
			LENGTH (MM)	WIDTH (MM)	HEIGHT (MM)	TARE WEIGHT (KG)
APS2KL	2000	1900	1416	2191	1330	1550
APS4.5KL	4500	4250	2925	2191	1330	2450
APS6.3KL	6300	6000	3870	2191	1330	3100
APS10KL	10000	9500	5800	2191	1330	4300
APS20KL	20000	19000	6058	2438	2896	6370
APS50KL	50000	47500	12192	2438	28961	2900
APS60KL	60000	57000	12192	2438	2896	12900

All Tanks are 110% Bunded for safe filling and spillages.

Picture shown above is only for illustration purpose, May contain optional item. In line with our Policy of continuous development, we reserve the right to change specification without notice. \* For more technical information, please refer to the website below:

[www.apsuae.com](http://www.apsuae.com)